

TAC-12CHSD/TPG21IH

Sound power level (inside)	51	dB(A)
Sound power level (outside)	60	dB(A)

Refrigerante R32 **GWP**

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contributeless to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 675. This means that if 1kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 675 times higher than 1kg of CO2, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

Cooling mode

6.1 A" SEER Energy efficiency class 3.4 kW Design load (Pdesignc)

195 kWh per year, based on standard test results. Energy consumption,

Actual energy consumption will depend on how the appliance is used and where it is located.

Heating mode (Average)

4.0 SCOP Energy efficiency class A* 2.4 (-10°C) Design load (Pdesignh) kW 2.2 (-10°C) kW Declared capacity Back up heating capacity 0.2 kW (-10°C)

Energy consumption, 840 kWh per year.based on standard test results.

Actual energy consumption will depend on how the appliance is used and where it is located.

Heating mode (Warmer) Optional

5.1 SCOP A*** Energy efficiency class 2.6 Design load (Pdesignh)

kW (2°C) Declared capacity 2.6 kW (2°C) Back up heating capacity 0 kW (2°C)

Energy consumption, 714 kWh per year.based on standard test results.

Actual energy consumption will depend on how the appliance is used and where it is located.

Heating mode (Colder) Optional

SCOP

Energy efficiency class

Design load (Pdesignh) kW (-22°C) Declared capacity kW (-22°C) Back up heating capacity kW (-22°C)

Energy consumption, kWh per year.based on standard test results.

Actual energy consumption will depend on how the appliance is used and where it is located.